

RKMTL-8U-22-HDV

1080p
Full HD



FC CE



Display Features & Benefits

- 8U rackmount 21.5" widescreen LCD
- Support **Full HD** with 1080p resolution
- Green LED-backlit panel technology
- PIP & Picture by Picture viewing efficiency
- VESA and Rackmount multiple hole mounting
- Ideal for CCTV security & industrial control


Options

- 3G / HD / SD-**SDI** Broadcast-grade input
- **MCS** Multi-display control solution
- F21" Touchscreen : Capacitive, Resistive, Multi-touch
- S-Video + Composite (BNC) or Audio input
- 48V, 24V or 12VDC power
- MIL-type or lockable connector

Basic I/O : DVI-D + VGA + HDMI w/ speaker
AV3.0 upgrade : DVI-D + VGA + HDMI + BNC + S-Video + audio
Options : SDI, USB for touchscreen & DC power

Specifications

• LCD Panel

Manufacturer : 

Size (diagonal) : 21.5" widescreen TFT

Max resolution : 1920 x 1080

Brightness (cd/m2) : 250

Backlight : LED

Colors : 16.7 M

Contrast ratio (typ) : 1000 : 1

Viewing angle (H/V) : 170° x 160°

Active area (mm) : 477 x 268

MTBF (hrs) : 30,000

Signal input : VGA, DVI-D and HDMI

• **Sound** : 2 x 2W Power

• Weight

Net : 10 kgs
(22 lbs)

Gross : 13 kgs
(29 lbs)

• Environmental

Operating : 0 to 50°C Degree

Storage : -5 to 60°C Degree

Relative humidity : 5~90%, non-condensing

Shock : 10G acceleration (11 ms duration)

Vibration : 5~500Hz 1G RMS random vibration

• Casing Color :

Black front panel (RAL 9005)
 Dark grey rear case (RAL 7037)

• Mounting :

Rackmount, 8U
 VESA mount, 100*100mm

• Regulatory :

FCC, CE

• Power

Input : Auto-sensing 100 to 240VAC, 50 / 60Hz

Consumption : Max. 48 Watt, Standby 5 Watt

• Dimensions

Product : 501.9 x 64.4 x 353 mm / 19.8 x 2.5 x 13.9 inch

Packing : 555 x 124 x 537 mm / 21.9 x 4.9 x 21.1 inch

Diagrams (mm)

